



All dimensions are in inches.
These flanges will be supplied with a 1/16" raised face unless otherwise specified.
Flat face option available.

ASME B16.47 Class 150 Series A Blind Flanges

Nominal Pipe Size	Outside Diameter (O)	Minimum Thickness (T)	Raised Face Diameter (R)	Approximate Weight (lbs)	Bolt Circle (C)	Number of Holes	Diameter of Holes
26	34.25	2.69	29.50	702	31.75	24	1.38
28	36.50	2.81	31.50	833	34.00	28	1.38
30	38.75	2.94	33.75	982	36.00	28	1.38
32	41.75	3.19	36.00	1238	38.50	28	1.62
34	43.75	3.25	38.00	1384	40.50	32	1.62
36	46.00	3.56	40.25	1676	42.75	32	1.62
38	48.75	3.44	42.25	1819	45.25	32	1.62
40	50.75	3.56	44.25	2040	47.25	36	1.62
42	53.00	3.81	47.00	2380	49.50	36	1.62
44	55.25	4.00	49.00	2715	51.75	40	1.62
46	57.25	4.06	51.00	2961	53.75	40	1.62
48	59.50	4.25	53.50	3350	56.00	44	1.62
50	61.75	4.38	55.50	3716	58.25	44	1.88
52	64.00	4.56	57.50	4156	60.50	44	1.88
54	66.25	4.75	59.50	4639	62.75	44	1.88
56	68.75	4.88	62.00	5130	65.00	48	1.88
58	71.00	5.06	64.00	5675	67.25	48	1.88
60	73.00	5.19	66.00	6155	69.25	52	1.88