



All dimensions are in inches.
These flanges will be supplied with a 1/16" raised face unless otherwise specified.
Flat face option available.

ASME B16.47 Class 300 Series B Blind Flanges

<u>Nominal Pipe Size</u>	<u>Outside Diameter (O)</u>	<u>Minimum Thickness (T)</u>	<u>Raised Face Diameter (R)</u>	<u>Approximate Weight (lbs)</u>	<u>Bolt Circle (C)</u>	<u>Number of Holes</u>	<u>Diameter of Holes</u>
26	34.12	3.50	29.00	905	31.62	32	1.38
28	36.25	3.50	31.00	1023	33.75	36	1.38
30	39.00	3.69	33.25	1250	36.25	36	1.50
32	41.50	4.06	35.50	1556	38.50	32	1.62
34	43.62	4.06	37.50	1719	40.62	36	1.62
36	46.12	4.06	39.75	1920	42.88	32	1.75
38	48.12	4.38	41.75	2257	44.88	36	1.75
40	50.12	4.56	43.88	2550	46.88	40	1.75
42	52.50	4.69	46.00	2875	49.00	36	1.88
44	54.50	5.00	48.00	3305	51.00	40	1.88
46	57.50	5.12	50.00	3766	53.75	36	2.00
48	59.50	5.31	52.25	4183	55.75	40	2.00
50	61.50	5.50	54.25	4629	57.75	44	2.00
52	63.50	5.68	56.25	5096	59.75	48	2.00
54	65.88	5.88	58.25	5679	62.12	48	2.00
56	69.50	6.18	60.50	6642	65.00	36	2.38
58	71.94	6.38	62.75	7347	67.44	40	2.38
60	73.94	6.56	65.00	7980	69.44	40	2.38