



All dimensions are in inches.
1/4" raised face will be added to the thickness unless otherwise specified.
Flat face option available.

ASME B16.47 Class 600 Series A Blind Flanges

Nominal Pipe Size	Outside Diameter (O)	Minimum Thickness (T)	Raised Face Diameter (R)	Approximate Weight (lbs)	Bolt Circle (C)	Number of Holes	Diameter of Holes
26	40.00	4.94	29.50	1760	36.00	28	2.00
28	42.25	5.19	31.50	2061	38.00	28	2.12
30	44.50	5.50	33.75	2423	40.25	28	2.12
32	47.00	5.81	36.00	2858	42.50	28	2.38
34	49.00	6.06	38.00	3237	44.50	28	2.38
36	51.75	6.38	40.25	3800	47.00	28	2.62
38	50.00	6.12	41.50	3405	45.75	28	2.38
40	52.00	6.38	43.75	3838	47.75	32	2.38
42	55.25	6.75	46.00	4585	50.50	28	2.62
44	57.25	7.00	48.25	5105	52.50	32	2.62
46	59.50	7.31	50.25	5758	54.75	32	2.62
48	62.75	7.69	52.50	6737	57.50	32	2.88
50	65.75	8.00	54.50	7695	60.00	28	3.12
52	67.75	8.25	56.50	8425	62.00	32	3.12
54	70.00	8.56	58.75	9333	64.25	32	3.12
56	73.00	8.88	60.75	10,530	66.75	32	3.38
58	75.00	9.12	63.00	11,414	68.75	32	3.38
60	78.50	9.56	65.25	13,108	71.75	28	3.62