



All dimensions are in inches.  
1/4" raised face will be added to the thickness and overall length unless otherwise specified.  
38" thru 60" sizes are the same as Series "A".  
Flat face option available.

### ASME B16.47 Class 600 Series B Welding Neck Flanges

Nominal Pipe Size	Outside Diameter (O)	Minimum Thickness (T)	Raised Face Diameter (R)	Length Thru Hub (Y)	Hub Diameter (X)	Minimum Fillet Radius (r)	Top of Hub (A)	Approximate Weight (lbs)	Bolt Circle (C)	Number of Holes	Diameter of Holes
26	35.00	4.38	28.62	7.12	27.50	0.50	26.00	550	31.75	28	1.75
28	37.50	4.56	30.88	7.50	29.62	0.50	28.00	650	34.00	28	1.88
30	40.25	4.94	33.12	8.06	31.75	0.50	30.00	810	36.50	28	2.00
32	42.75	5.12	35.25	8.50	33.88	0.50	32.00	950	38.75	28	2.12
34	45.75	5.56	37.50	9.19	36.00	0.56	34.00	1205	41.50	24	2.38
36	47.75	5.75	39.75	9.56	38.12	0.56	36.00	1340	43.50	28	2.38
38	<p><b>SAME DIMENSIONS AS 600# SERIES "A"</b></p>										
40											
42											
44											
46											
48											
50											
52											
54											
56											
58											
60											