



All dimensions are in inches.
These flanges will be furnished with a 1/16" raised face unless otherwise specified.

INDUSTRY STANDARD CLASS 125/150 SLIP-ON FLANGES

Nominal Pipe Size	Outside Diameter (O)	Thickness (T)	Overall Thickness (Y)	Hub Diameter (X)	Inside Diameter (B)	Number of Bolt Holes	Diameter of Bolt Holes	Diameter of Bolt Circle (C)	Approximate Weight (lbs)
26	34.25	2.00	3.38	28.50	26.25	24	1.38	31.75	235
28	36.50	2.06	3.44	30.75	28.25	28	1.38	34.00	270
30	38.75	2.13	3.50	32.75	30.25	28	1.38	36.00	305
32	41.75	2.25	3.63	35.00	32.25	28	1.63	38.50	375
34	43.75	2.31	3.69	37.00	34.25	32	1.63	40.50	400
36	46.00	2.38	3.75	39.25	36.25	32	1.63	42.75	450
38	48.75	2.38	3.75	41.75	38.25	32	1.63	45.25	530
40	50.75	2.50	3.88	43.75	40.25	36	1.63	47.25	570
42	53.00	2.63	4.00	46.00	42.25	36	1.63	49.50	650
44	55.25	2.63	4.00	48.00	44.25	40	1.63	51.75	690
46	57.25	2.69	4.06	50.00	46.25	40	1.63	53.75	730
48	59.50	2.75	4.13	52.25	48.25	44	1.63	56.00	800
50	61.75	2.75	4.13	54.25	50.25	44	1.88	58.25	830
52	64.00	2.88	4.25	56.50	52.25	44	1.88	60.50	920
54	66.25	3.00	4.38	58.75	54.25	44	1.88	62.75	1025
60	73.00	3.13	4.50	65.25	60.25	52	1.88	69.25	1250
66	80.00	3.38	4.88	71.50	66.25	52	1.88	76.00	1625
72	86.50	3.50	5.00	78.50	72.25	60	1.88	82.50	1925
78	93.00	3.88	5.38	84.50	78.25	64	2.13	89.00	2525
84	99.75	3.88	5.38	90.50	84.25	64	2.13	95.50	2600
90	106.50	4.25	5.75	96.75	90.25	68	2.38	102.00	3150
96	113.25	4.25	5.75	102.75	96.25	68	2.38	108.50	3275