



All dimensions are in inches.
These flanges will be supplied with a 1/16" raised face unless otherwise specified.
Dimensions are supportive from industry terminology and are a non-committee specification.
These flanges are not covered by ASME B16.47 or API-605 specifications.

Nominal Pipe Size	Outside Diameter (O)	Thickness (T)	Raised Face Diameter (R)	Length Thru Hub (Y)	Hub Diameter (X)	Minimum Fillet Radius (r)	Flange Bore (B)	Number of Holes	Diameter of Holes	Bolt Circle (C)	Approximate Weight (lbs)
26	30.94	1.62	28.00	2.62	26.94	0.38	26.25	36	0.88	29.31	85
28	32.94	1.75	30.00	2.75	28.94	0.38	28.25	40	0.88	31.31	97
30	34.94	1.75	32.00	2.75	31.00	0.38	30.25	44	0.88	33.31	103
32	37.06	1.81	34.00	2.81	33.06	0.38	32.25	48	0.88	35.44	125
34	39.56	1.94	36.25	2.94	35.12	0.38	34.25	40	1.00	37.69	165
36	41.62	2.06	38.25	3.06	37.19	0.38	36.25	44	1.00	39.75	186
38	44.25	2.12	40.25	3.12	39.25	0.38	38.25	40	1.12	42.12	227
40	46.25	2.19	42.50	3.19	41.31	0.38	40.25	44	1.12	44.12	245
42	48.25	2.31	44.50	3.31	43.38	0.44	42.25	48	1.12	46.12	269
44	50.25	2.38	46.50	3.38	45.38	0.44	44.25	52	1.12	48.12	288
46	52.81	2.44	48.62	3.44	47.44	0.44	46.25	40	1.25	50.56	343
48	54.81	2.56	50.75	3.56	49.50	0.44	48.25	44	1.25	52.56	373
50	56.81	2.69	52.75	3.69	51.50	0.44	50.25	48	1.25	54.56	403
52	58.81	2.75	54.75	3.75	53.56	0.44	52.25	52	1.25	56.56	426
54	61.00	2.81	56.75	3.81	55.62	0.44	54.25	56	1.25	58.75	469
56	63.00	2.88	58.75	3.88	57.69	0.56	56.25	60	1.25	60.75	492
58	65.94	2.94	60.75	3.94	59.69	0.56	58.25	48	1.38	63.44	602
60	67.94	3.00	63.00	4.00	61.81	0.56	60.25	52	1.38	65.44	634