



All dimensions are in inches.  
These flanges will be supplied with a 1/16" raised face unless otherwise specified.  
Dimensions are supportive from industry terminology and are a non-committee specification.  
These flanges are not covered by ASME B16.47 or MSS-SP44 specifications.

**INDUSTRY STANDARD CLASS 150 SERIES "A" SLIP-ON FLANGES (BOLTING MATCHES)**

Nominal Pipe Size	Outside Diameter (O)	Thickness (T)	Raised Face Diameter (R)	Length Thru Hub (Y)	Hub Diameter (X)	Minimum Fillet Radius (r)	Flange Bore (B)	Number of Bolt Holes	Diameter of Bolt Holes	Diameter of Bolt Circle (C)	Approximate Weight (lbs)
26	34.25	2.69	29.50	3.69	28.25	0.38	26.25	24	1.38	31.75	235
28	36.5	3.06	31.50	3.81	30.50	0.44	28.25	28	1.38	34	270
30	38.75	3.31	33.75	3.94	32.50	0.44	30.25	28	1.38	36	305
32	41.75	3.41	36.00	4.18	34.50	0.44	32.25	28	1.63	38.5	375
34	43.75	3.68	38.00	4.25	36.50	0.50	34.25	32	1.63	40.5	400
36	46	3.96	40.25	4.56	38.75	0.50	36.25	32	1.63	42.75	450
38	48.75	4.06	42.25	4.56	41.25	0.50	38.25	32	1.63	45.25	530
40	50.75	4.18	44.25	4.81	43.25	0.50	40.25	36	1.63	47.25	570
42	53	4.43	47.00	5.06	45.50	0.50	42.25	36	1.63	49.5	650
44	55.25	4.68	49.00	5.18	47.75	0.50	44.25	40	1.63	51.75	690
46	57.25	4.86	51.00	5.31	49.75	0.50	46.25	40	1.63	53.75	730
48	59.5	5.06	53.50	5.56	52.00	0.50	48.25	44	1.63	56	800