



All dimensions are in inches.
These flanges will be supplied with a 1/16" raised face unless otherwise specified.
Dimensions are supportive from industry terminology and are a non-committee specification.
These flanges are not covered by ASME B16.47 or MSS-SP44 specifications.

INDUSTRY STANDARD CLASS 300 SERIES "A" SLIP-ON FLANGES (BOLTING MATCHES)

Nominal Pipe Size	Outside Diameter (O)	Thickness (T)	Raised Face Diameter (R)	Length Thru Hub (Y)	Hub Diameter (X)	Bore (B)	Minimum Fillet Radius (r)	Number of Holes	Diameter of Holes	Bolt Circle (C)	Approximate Weight (lbs)
26	38.25	3.12	29.50	5.37	30.25	26.25	0.38	28	1.75	34.50	595
28	40.75	3.38	31.50	5.68	32.75	28.25	0.44	28	1.75	37.00	729
30	43.00	3.62	33.75	6.12	34.75	30.25	0.44	28	1.88	39.25	840
32	45.25	3.88	36.00	6.56	36.75	32.25	0.44	28	2.00	41.50	964
34	47.50	4.00	38.00	6.81	38.75	34.25	0.50	28	2.00	43.50	1076
36	50.00	4.12	40.25	7.06	41.00	36.25	0.50	32	2.12	46.00	1202
38	46.00	5.31	40.50	6.06	39.00	38.25	0.50	32	1.62	43.00	687
40	48.75	5.56	42.75	6.56	41.25	40.25	0.50	32	1.75	45.50	840
42	50.75	5.81	44.75	6.81	43.25	42.25	0.50	32	1.75	47.50	922
44	53.25	6.06	47.00	6.86	45.25	44.25	0.50	32	1.88	49.75	1055
46	55.75	6.31	49.00	7.06	47.25	46.25	0.50	28	2.00	52.00	1205
48	57.75	6.56	51.25	7.18	49.25	48.25	0.50	32	2.00	54.00	1306